

perfSONAR: A SERVICE ORIENTED ARCHITECTURE FOR MULTI-DOMAIN NETWORK MONITORING

Szymon Trocha, Poznań Supercomputing and Networking Centre

TERENA NRENs and Grids Workshop, Amsterdam, 15 Sep 2010

The research leading to these results has received funding from the European Community's Seventh Framework Programme (FP7/2007-2013) under grant agreement no 238875 (GÉANT)



Performance Measurement Goals



- Increase network awareness
 - Promote realistic expectations of network amongst users
- Reduce diagnostic costs
 - Performance problems noticed early
 - Performance problems addressed efficiently
 - Network engineers can see & act outside their domains
- Transform application design
 - Applications designed with networks in mind





Four Aspects to perfSONAR




- Architecture and protocols
 - Define web services based on roles
 - Define their communication syntax and semantics
 - Protocols based on the Open Grid Forum (OGF) Network
 Measurement Working Group (NM-WG) schemas
 - Allow anyone to develop web service implementations
- A set of interoperable software implementations.
 - Java, Perl, Python etc.
- A collaboration by many organisations
- A deployed measurement infrastructure





perfSONAR as unifying layer across domains





perfSONAR Use Cases



- Come from international community of European and American research networks
- Help to systematize requirements coming from other communities
- Shift focus from adding features to perfSONAR products to delivering perfSONAR products to communities as a service
- Help to better integrate perfSONAR components development
- The perfSONAR infrastructure supports use cases in terms of delivered functionality





Network Performance and Diagnostic GÉANT



- Service: Enables users at the edge of the network to identify performance capabilities and leverage the people and tools necessary to improve their end-to-end experience
- Users: performance engineers at NRENs, national and regional backbones
- **Functionalities**
 - Link availability (L2, L3)
 - Available bandwidth (historical/on-demand, UDP/TCP)
 - One-way delay, one-way delay variation
 - **Traceroute**
 - Ping
- Measurement Points
 - Discoverable
 - Available and accessible
 - Intra-domain, inter-domain and multi-domain paths
 - Integrated into workflows

Network Characterization Use Case



- Service: Makes it easy for large experiments/projects to monitor their paths of interest, and be able to identify the attributes of those end-toend multidomain paths
- Users: NOC engineers and key people responsible for a large experiments data movement (e.g. Virtual Organizations)
- Functionalities
 - Path uptime
 - Router interface utilization, drops, and errors
 - Achievable bandwidth (end-to-end and network-to-network)
 - Packet loss / reordering / one-way delay variation (end-to-end and network-to-network)
- Data visualization tools to easily combine all data

Dynamic Circuit Monitoring Use Case GÉANT



- Service: Enables the automatic creation and monitoring of multi-domain dynamic circuits within the set of participanting networks
- Users: NOC engineers, power users such as project virtual NOCs
- **Functionalities**
 - Notifications (flexibly configurable, triggered by changes in state)
 - Cover current and historic state
 - Cover administrative and operational states
- Measurement Points
 - Must be reliable
 - Configuration must be automated
 - Must scale to static and dynamic circuits
 - Information model must support reporting about any potential performance metric for the following
 - Full circuit
 - Each segment
 - Each link or interface

Web Portal for End Users Use Case



- How am I doing?
- Is it even possible to do this?
 - If yes
 - Is this better/worse than others?
 - If worse, what's then?
 - Educate
 - Ask for help





GÉANT Monitoring Services



- perfSONAR MDM Basic
 - Software (perfSONAR components) and support (Service Desk)
 - Effective federated model for NRENs and regional networks
 - Domains deploy necessary components using their own infrastructure and resources
- perfSONAR MDM Managed
 - Infrastructure (measurement servers), software (perfSONAR components), support and maintenance (Service Desk)
 - Effective solution for private networks
 - Implemented for LHCOPN
- perfSONAR MDM Passive
 - Dedicated infrastructure for passive network monitoring (dedicated optical cards), software and support





perfSONAR Suite



- Web services
 - Measurement Archives (MA)
 - RRD MA, SQL MA, HADES MA
 - Lookup Service
 - Auth/Autz
- Measurement Point services (MP)
 - BWCTL MP, SSH/Telnet MP, E2EMon MP
- Visualization
 - Different ways of using infrastructure and presenting data





Available In Production



- perfSONAR MDM 3.2 release
 - Bundle of perfSONAR MDM installers comprising Java and Perl web services as well as administrator's documentation
 - DEB, RPM installation packages
 - Originated in GÈANT
- Visualization tools
- Coming soon: perfSONAR MDM 3.3 release
 - Better performance and stability
 - DVD installation







http://www.perfsonar.net

szymon.trocha@psnc.pl

